

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-21089-W

August 8, 2020

GT-21089-W

Information

Model Number	GT-21089-W
Description	GT-21089-W, ITE Power Supply, Wall Plug-in, Regulated Switchmode AC-DC Power Supply AC Adaptor, , Input Rating: 100-240V~, 50-60 Hz, , Output Rating: 19 Watts, Power rating with convection cooling (W) , 3.3-48V in 0.1V increments, Approvals:

Model Picture



Agency Documents	http://www.globtek.info/certs/GT-21089/
CE EC-Declaration	https://www.globtek.com/pdf/ec_declaration/a0O3000007P7YREA0
RoHS/RoHS2 Declaration	https://www.globtek.com/pdf/rohs_cert/a0O3000007P7YREA0
REACH Declaration	https://www.globtek.com/pdf/iso_certificates/REACH.pdf
Conflict Minerals Declaration	https://www.globtek.com/pdf/conflict-minerals.pdf

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-21089-W

August 8, 2020

MODEL PARAMETERS

Type	Wall Plug-in
Technology	Regulated Switchmode AC-DC Power Supply AC Adaptor
Category	ITE Power Supply
Input Voltage	100-240V~, 50-60 Hz
I/P Amps (A)	
Wattage (W)	19.0
Vout Range (V)	3.3-48
Efficiency Level	
Ingress Protection	
Size (mm)	74*49*40.5

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-21089-W

August 8, 2020

ENCLOSURE

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-21089-W

August 8, 2020

RATING TABLE

Model Number	Voltage	Amps(A)	Watts(W)	RFQ
GT-21089-1512-W3	12 V	1.25	15.00	RFQ

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-21089-W

August 8, 2020

SPECIFICATIONS

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-21089-W

August 8, 2020

DERATING CURVE

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-21089-W

August 8, 2020

INPUT CONFIGURATION

Delivering leading edge, innovative power solutions for more than 30 years....

Model:GT-21089-W

August 8, 2020

OUTPUT CONFIGURATION

Common output connector options:


 L Type (Coaxial
5.5x2.5mm plug)

 C Type (Coaxial
5.5x2.1mm plug)

 K Type (Coaxial
3.5x1.3mm plug)

 LL Type (5.5x2.5mm
Locking 760k type)

 CL Type (5.5x2.1mm
Locking S761k type)

 ML2 Type (Molex
housing 43025-0200)

 YL3 Type
(KPPX-3P)


YL4 Type (KPPX-4P)


 EJ1/2/3/4/5 (EIAJ
RC-5320A type
connectors)

 MSB Type (Micro
USB)

 USBC Type (USB
Type C)

 Inquire for custom
design

 For a comprehensive list of options, [click here](#)

Contact GlobTek for your specific requirements or custom solutions.

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-21089-W

August 8, 2020

Approvals

Logo	
------	--