

Delivering leading edge, innovative power solutions for more than 30 years....

Model:GT-91080

April 10, 2020

POE Splitter, 12w, available in outputs of 5-24VDC, (IEEE802.3af PoE PD)

Information

Model Number

GT-91080

Description

GT-91080, Af type PoE Splitter, Desktop/External, Power Over Ethernet Powered Device Converter (IEEE802.3af PoE PD) Power Supply AC Adaptor, , Input Rating: 36-60 VDC, , Output Rating: 12 Watts, Power rating with convection cooling (W) , 5-24V in 0.1V increments, Approvals:

Model Picture



Agency Documents

CE EC-Declaration

https://www.globtek.com/pdf/ec_declaration/a0O3000007P7YqEAK

RoHS/RoHS2 Declaration

https://www.globtek.com/pdf/rohs_cert/a0O3000007P7YqEAK

REACH Declaration

https://www.globtek.com/pdf/iso_certificates/REACH.pdf

Conflict Minerals Declaration

<https://www.globtek.com/pdf/conflict-minerals.pdf>

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-91080

April 10, 2020

MODEL PARAMETERS

Type	Desktop/External
Technology	Power Over Ethernet Powered Device Converter (IEEE802.3af PoE PD) Power Supply AC Adaptor
Category	Af type PoE Splitter
Input Voltage	36-60 VDC
I/P Amps (A)	0.4
Wattage (W)	12.0
Vout Range (V)	5-24
Efficiency Level	
Ingress Protection	
Size (mm)	85*76*36

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-91080

April 10, 2020

ENCLOSURE

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-91080

April 10, 2020

RATING TABLE

Model Number	Voltage	Amps(A)	Watts(W)	RFQ
GT-91080-1005	5 V	2	10.00	RFQ
GT-91080-1006	6 V	2	12.00	RFQ
GT-91080-0812	12 V	0.666	7.99	RFQ
GT-91080-1212	12 V	1	12.00	RFQ
GT-91080-1215	15 V	0.8	12.00	RFQ
GT-91080-0818	18 V	0.444	7.99	RFQ
GT-91080-1218	18 V	0.666	11.99	RFQ
GT-91080-1220	20 V	0.6	12.00	RFQ
GT-91080-0824	24 V	0.333	7.99	RFQ
GT-91080-1224	24 V	0.5	12.00	RFQ

Model:GT-91080

April 10, 2020

SPECIFICATIONS

A) ELECTRICAL SPECIFICATIONS:

01. DC Input Voltage: 36 – 60V
02. Output Regulation: +/- 5% measured at the output connector
03. Line Voltage Regulation: +/- 0.2% typical measured at the output connector
04. Output Ripple (Vp-p): 1% or 100mV max, measured at 20 MHz bandwidth with 0.1 uf ceramic capacitor in parallel with a low impedance 47 uf electrolytic capacitor connected at the output
05. Switching Frequency: 100 KHz typical
06. Efficiency : 80% typ

B) PROTECTION

01. Under Voltage Lockout: 30Vdc
02. Short Circuit: Protected unit will auto recover upon removal of fault
03. Current Limiting: 110% to 175% of output rating
04. Thermal: Internally protected against over-temperature conditions

C) SAFETY & EMC

01. Isolation Voltage : 1000Vdc
02. Isolation Resistance :100M ohms (min)
03. Designed to UL/EN/IEC 60950-1
04. Meet FCC Class B standard
05. Meet EN55022 Class B standard

D) OTHER:

01. MTBF: 200,000 Hours @ 25°C ambient temperature
02. Operating Temperature: -15°C to 60°C ambient temperature
03. Humidity: 0% to 90% relative humidity
04. Storage Temperature: -40°C to 85°C
05. Cooling: Free air cooling
06. Interoperability: Complies with IEEE 802.3 AF, tested by UNH-iOL
07. Input Set Classification Resistance : 24.9K ohms
08. Ethernet Communications Data Rates: 10/100 BaseT

E) ENCLOSURE

01. SIZE : 85*76*36 (L*W*H)m/m
02. Weight: 110g
03. Markings: Label and/or Pad Printed and/or Molded in the case

F) OPTIONS

01. Tighter output voltage regulation, +/- 2% or +/-3%
02. Reduced Vp-p Output Ripple
03. Custom Output Voltage, in 0.1V increment

G) INTERCONNECTS

01. RJ45 Input Power: Power received on either pairs 4-5/7-8 or 1-2/3-6.
02. RJ45 Input Communications: Received on standard pins 1-2/3-6 used for 10/100 BaseT Ethernet

PROPRIETARY INFORMATION

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC.

<http://en.globtek.com/datasheet/id/a0030000007P7Yq>

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-91080

April 10, 2020

03. RJ45 Output Communications: Ethernet passed thru on pins 1-2/3-6

03. Output Cable: DC power delivered thru 300mm length 18 gauge UL1185 style cable to a standard 2.5 x 5.5 x 11mm DC Power Plug, Center Positive

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-91080

April 10, 2020

DERATING CURVE

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-91080

April 10, 2020

INPUT CONFIGURATION

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-91080

April 10, 2020

Approvals

Logo	
------	--